

UNIROYAL[®] HS50[™]

The Uniroyal[®] HS50[™] gives you what you want in an on/off road steer/all-position tire.

- A TOUGH, RELIABLE TREAD COMPOUND THAT FIGHTS CHIPS AND CUTS

- LONG, WORRY-FREE TREAD LIFE

- A RETREADABLE TIRE REINFORCED WITH DuraShield[™] HEAVY-DUTY CONSTRUCTION

- AN AFFORDABLE, RELIABLE TIRE FROM A BRAND YOU KNOW AND TRUST




Size	Load Range	Catalog Number	Tread Depth 32nds	Max. Speed * km/h	Loaded Radius		Overall Diameter		Overall Width ‡		Approved Rims Ø	Min. Dual Spacing ‡		Revs Per Mile	Max. Load Per Tire Single				Max. Load Per Tire Dual			
					in.	mm	in.	mm	in.	mm		in.	mm		lb.	psi	kg.	kPa	lb.	psi	kg.	kPa
11R22.5	H	75563	20	105	19.5	495	41.5	1,056	11.1	281	8.25, 7.50	12.5	318	497	6,610	120	3,000	830	6,005	120	2,725	830
315/80R22.5	L	32343	20	105	19.8	503	42.4	1,076	12.5	318	9.00, 8.25	113.8	351	510	9,090	130	4,125	900	8,270	130	3,750	900
425/65R22.5†	L	24111	20	105	20.8	528	44.3	1,125	16.6	422	13.00, 12.25	—	—	486	11,400	120	5,150	830	—	—	—	—
11R24.5	H	46845	20	105	20.4	519	43.5	1,106	11.1	281	8.25, 7.50	12.5	318	475	7,160	120	3,250	830	6,610	120	3,000	830

* Exceeding the lawful speed limit is neither recommended nor endorsed.

‡ Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

Ø Note: Wheel listed first is the measuring wheel.

† HS50 Wide Base tread design.



DuraShield[™] HEAVY-DUTY CONSTRUCTION

Uniroyal's unique features of pyramidal steel belt construction with an additional summit ply, insulating belt edge strips, and heavy gauge inner liner combine to deliver the durability and retreadability you want in a truck tire.

