

UNIROYAL[®] LS24[™]

The Uniroyal[®] LS24[™] gives you what you want in a long haul steer/all-position tire.



- A LONG-LASTING, SmartWay[®] VERIFIED TIRE

- A TIRE DESIGNED TO COMBAT IRREGULAR WEAR



- A RETREADABLE TIRE WITH DuraShield[™] CONSTRUCTION


- AN AFFORDABLE, RELIABLE TIRE FROM A BRAND YOU KNOW AND TRUST

Size	Load Range	Catalog Number	Tread Depth 32nds	Max. Speed * km/h	Loaded Radius		Overall Diameter		Overall Width ‡		Approved Rims Ø	Min. Dual Spacing ‡		Revs Per Mile	Max. Load Per Tire Single				Max. Load Per Tire Dual			
					in.	mm	in.	mm	in.	mm		in.	mm		lb.	psi	kg	kPa	lb.	psi	kg	kPa
11R22.5	G	56682	18	120	19.2	488	41.1	1,047	11.0	279	8.25, 7.50	12.5	318	503	6,175	105	2,800	720	5,840	105	2,650	720
275/80R22.5	G	63171	18	120	18.4	466	39.5	1,003	10.8	274	8.25, 7.50	12.2	311	549	6,175	110	2,800	760	5,675	110	2,575	760
11R24.5	G	06873	18	120	20.2	515	43.2	1,099	11.0	280	8.25, 7.50	12.5	318	497	6,610	105	3,000	720	6,005	105	2,725	720
275/80R24.5	G	90905	18	120	19.4	492	41.5	1,054	10.8	274	8.25, 7.50	12.2	311	521	6,175	110	2,800	760	5,675	110	2,575	760

* Exceeding the lawful speed limit is neither recommended nor endorsed.

‡ Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

Ø Note: Wheel listed first is the measuring wheel.



DuraShield[™] CONSTRUCTION

Uniroyal's unique features of pyramidal steel belt construction, insulating belt edge strips, and heavy gauge inner liner combine to deliver the durability and retreadability you want in a truck tire.

