

# UNIROYAL® RS20™

The Uniroyal® RS20™ gives you what you want in a regional steer/all-position tire.



- A LONG-LASTING, SmartWay® VERIFIED TIRE

- A TOUGH, SOLID SHOULDER THAT FIGHTS SCRUB



- A RETREADABLE TIRE WITH DuraShield™ CONSTRUCTION


- AN AFFORDABLE, RELIABLE TIRE FROM A BRAND YOU KNOW AND TRUST

Size	Load Range	Catalog Number	Tread Depth 32nds	Max. Speed * km/h	Loaded Radius		Overall Diameter		Overall Width ‡		Approved Rims Ø	Min. Dual Spacing ‡		Revs Per Mile	Max. Load Per Tire Single				Max. Load Per Tire Dual			
					in.	mm	in.	mm	in.	mm		in.	mm		lb.	psi	kg	kPa	lb.	psi	kg	kPa
11R22.5	H	98533	18	120	19.2	488	41.2	1,047	11.0	280	8.25, 7.50	12.5	318	525	6,610	120	3,000	830	6,005	120	2,725	830
255/70R22.5	H	10090	17	120	16.8	427	36.4	923	10.2	258	8.25, 7.50	11.6	295	601	5,510	120	2,500	830	5,070	120	2,300	830
275/80R22.5	H	42794	18	120	18.3	465	39.4	1,001	10.8	274	8.25, 7.50	12.2	311	551	6,610	120	3,000	830	6,005	120	2,725	830
11R24.5	H	05339	18	120	20.2	515	43.2	1,099	11.0	280	8.25, 7.50	12.5	318	497	7,160	120	3,250	830	6,610	120	3,000	830
275/80R24.5	H	12501	18	120	19.3	491	41.4	1,052	10.8	274	8.25, 7.50	12.2	311	522	6,780	120	3,075	830	6,175	120	2,800	830

\* Exceeding the lawful speed limit is neither recommended nor endorsed.

‡ Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

Ø Note: Wheel listed first is the measuring wheel.



## DuraShield™ CONSTRUCTION

Uniroyal's unique features of pyramidal steel belt construction, insulating belt edge strips, and heavy gauge inner liner combine to deliver the durability and retreadability you want in a truck tire.

