

Application Position	LONG HAUL 	REGIONAL 	ON/OFF ROAD 
Steer/ All Position	<p><b>UNIROYAL® LS24™</b>  <b>4 Year*</b> </p> <p>The Uniroyal® LS24™ gives you what you want in a long haul steer/all-position tire.</p> <ul style="list-style-type: none"> <li>• A long-lasting, SmartWay® verified tire</li> <li>• A tire designed to combat irregular wear</li> <li>• A retreadable tire with DuraShield® construction</li> <li>• An affordable, reliable tire from a brand you know and trust</li> </ul>	<p><b>UNIROYAL® RS20™</b>  <b>4 Year*</b> </p> <p>The Uniroyal® RS20™ gives you what you want in a regional steer/all-position tire.</p> <ul style="list-style-type: none"> <li>• A long-lasting, SmartWay® verified tire</li> <li>• A tough, solid shoulder that fights scrub</li> <li>• A retreadable tire with DuraShield® construction</li> <li>• An affordable, reliable tire from a brand you know and trust</li> </ul>	<p><b>UNIROYAL® HS50™</b> <small>Wide Base</small> </p> <p>The Uniroyal® HS50™ gives you what you want in an on/off road steer/all-position tire.</p> <ul style="list-style-type: none"> <li>• A tough, reliable tread compound that fights chips and cuts</li> <li>• Long, worry-free tread life</li> <li>• A retreadable tire reinforced with DuraShield® heavy-duty construction</li> <li>• An affordable, reliable tire from a brand you know and trust</li> </ul>
Drive Axle	<p><b>UNIROYAL® LD10™</b>  <b>4 Year*</b> </p> <p>A long-lasting, SmartWay® verified drive tire optimized for long haul applications.</p> <ul style="list-style-type: none"> <li>• A long-lasting, SmartWay® verified tire</li> <li>• Enhanced fuel-efficient compounding designed for even wear</li> <li>• Tiger Claw™ traction that grips the road</li> <li>• A retreadable tire with DuraShield® construction</li> <li>• An affordable, reliable tire from a brand you know and trust</li> </ul>	<p><b>UNIROYAL® RD30™</b> <b>4 Year*</b> </p> <p>The Uniroyal® RD30™ gives you what you want in a regional drive tire.</p> <ul style="list-style-type: none"> <li>• Long, worry-free tread life</li> <li>• Tiger Claw™ traction that grips the road</li> <li>• StoneBlocker™ design that protects the casing</li> <li>• A retreadable tire with DuraShield® construction</li> <li>• An affordable, reliable tire from a brand you know and trust</li> </ul>	<p><b>UNIROYAL® HD60™</b> </p> <p>The Uniroyal® HD60™ gives you what you want in an on/off road drive tire.</p> <ul style="list-style-type: none"> <li>• Tiger Claw™ traction grabs whatever surface you're working on</li> <li>• A tough, reliable tread compound that fights chips and cuts</li> <li>• StoneBlocker™ design that protects the casing</li> <li>• A retreadable tire reinforced with DuraShield® heavy-duty construction</li> <li>• An affordable, reliable tire from a brand you know and trust</li> </ul>
Trailer Axle	<p><b>UNIROYAL® LT40™</b>  <b>4 Year*</b> </p> <p>The Uniroyal® LT40™ gives you what you want in a long haul and regional trailer tire.</p> <ul style="list-style-type: none"> <li>• A long-lasting, SmartWay® verified tire that combats irregular wear</li> <li>• Stoneblocker™ design that protects the casing</li> <li>• A retreadable tire with DuraShield® construction</li> <li>• An affordable, reliable tire from a brand you know and trust</li> </ul>		<p><b>UNIROYAL® HS50™</b> </p> <p>The Uniroyal® HS50™ gives you what you want in an on/off road steer/all-position tire.</p> <ul style="list-style-type: none"> <li>• A tough, reliable tread compound that fights chips and cuts</li> <li>• Long, worry-free tread life</li> <li>• A retreadable tire reinforced with DuraShield® heavy-duty construction</li> <li>• An affordable, reliable tire from a brand you know and trust</li> </ul>

\* 4 Year / 1-Retread Manufacturer's Limited Casing Guarantee. See limited warranty for details.

# TECHNICAL DATA

Size	Tread	Load Range	Catalog Number	Tread Depth 32nds	Max. Speed (1) mph	Loaded Radius		Overall Diameter		Overall Width (2)		Approved Wheels (Measuring wheel listed first)	Min. Dual Spacing (2)		Revs Per Mile	Max. Load Per Tire Single				Max. Load Per Tire Dual			
						in.	mm.	in.	mm.	in.	mm.		in.	mm.		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
225/70R19.5	RD30	G	25102	18	75	15.2	387	32.4	824	9.2	234	6.00, 6.75	9.7	246	637	3970	110	1800	760	3750	110	1700	760
	RS20	G	40560	15	75	14.8	377	32.2	818	8.9	226	6.75, 6.00	10.0	254	646	3970	110	1800	760	3750	110	1700	760
245/70R19.5	RD30	G	97846	18	75	15.7	398	33.6	853	9.8	248	6.75, 7.50	10.9	273	617	4540	110	2060	760	4300	110	1950	760
	RS20	G	38164	16	75	15.3	388	33.3	846	9.7	246	6.75, 7.50	10.9	277	661	4540	110	2060	760	4300	110	1950	760
11R22.5	LS24	G	56682	18	75	19.2	488	41.1	1047	11.0	279	8.25, 7.50	12.5	318	503	6175	105	2800	720	5840	105	2650	720
	HD60	H	04591	28	65	19.7	501	42.0	1069	11.0	281	8.25, 7.50	12.5	318	492	6610	120	3000	830	6005	120	2725	830
	HS50	H	75563	20	65	19.5	495	41.5	1056	11.1	281	8.25, 7.50	12.5	318	497	6610	120	3000	830	6005	120	2725	830
	LD10	H	36979	26	75	19.6	497	41.8	1062	11.0	280	8.25, 7.50	12.5	318	529	6610	120	3000	830	6005	120	2725	830
	LT40	H	06756	12	75	19.0	484	40.8	1039	11.0	280	8.25, 7.50	12.5	318	529	6610	120	3000	830	6005	120	2725	830
	RD30	H	04433	26	75	19.5	497	41.7	1062	11.0	280	8.25, 7.50	12.5	318	516	6610	120	3000	830	6005	120	2725	830
	RS20	H	98533	18	75	19.2	488	41.2	1047	11.0	280	8.25, 7.50	12.5	318	525	6610	120	3000	830	6005	120	2725	830
255/70R22.5	RS20	H	10090	17	75	16.8	427	36.4	923	10.2	258	8.25, 7.50	11.6	295	601	5510	120	2500	830	5070	120	2300	830
275/80R22.5	LD10	G	39892	26	75	18.8	477	40.1	1018	10.8	274	8.25, 7.50	12.2	311	516	6175	110	2800	760	5675	110	2575	760
	LS24	G	63171	18	75	18.5	469	39.6	1006	10.7	273	8.25, 7.50	12.2	311	523	6175	110	2800	760	5675	110	2575	760
	LT40	G	15809	12	75	18.3	465	39.2	995	10.7	273	8.25, 7.50	12.2	311	529	6175	110	2800	760	5675	110	2575	760
	RD30	G	24327	26	75	18.8	477	40.1	1019	10.8	274	8.25, 7.50	12.2	311	516	6175	110	2800	760	5675	110	2575	760
	RS20	H	42794	18	75	18.3	465	39.4	1001	10.8	274	8.25, 7.50	12.2	311	551	6610	120	3000	830	6005	120	2725	830
315/80R22.5	HD60	L	37144	25	65	19.9	506	42.9	1089	12.6	320	9.00, 8.25	13.8	351	484	9090	130	4125	900	8270	130	3750	900
	HS50	L	32343	20	65	19.8	502	42.5	1080	12.6	319	9.00, 8.25	13.8	351	488	9090	130	4125	900	8270	130	3750	900
425/65R22.5 (3)	HS50 WB	L	24111	20	65	20.5	520	44.5	1130	16.6	421	12.25, 11.75, 13.00	—	—	468	11400	120	5150	830	—	—	—	—
11R24.5	LS24	G	06873	18	75	20.2	515	43.2	1099	11.0	280	8.25, 7.50	12.5	318	497	6610	105	3000	720	6005	105	2725	720
	HD60	H	58999	28	65	20.6	524	44.0	1119	11.1	283	8.25, 7.50	12.5	318	470	7160	120	3250	830	6610	120	3000	830
	HS50	H	46845	20	65	20.4	519	43.5	1106	11.1	281	8.25, 7.50	12.5	318	475	7160	120	3250	830	6610	120	3000	830
	LT40	H	10868	12	75	20.0	510	42.8	1089	11.0	280	8.25, 7.50	12.5	318	503	7160	120	3250	830	6610	120	3000	830
	RD30	H	91739	26	75	20.5	521	43.7	1112	11.0	280	8.25, 7.50	12.5	318	492	7160	120	3250	830	6610	120	3000	830
	RS20	H	05339	18	75	20.2	515	43.2	1099	11.0	280	8.25, 7.50	12.5	318	497	7160	120	3250	830	6610	120	3000	830
275/80R24.5	LS24	G	90905	18	75	19.4	495	41.5	1058	10.8	273	8.25, 7.50	12.2	311	521	6175	110	2800	760	5675	110	2575	760
	LT40	G	89212	12	75	19.4	492	41.2	1046	10.8	273	8.25, 7.50	12.2	311	527	6175	110	2800	760	5675	110	2575	760
	RD30	G	92294	25	75	19.8	502	42.1	1069	10.8	273	8.25, 7.50	12.2	311	515	6175	110	2800	760	5675	110	2575	760
	RS20	H	12501	18	75	19.3	491	41.4	1052	10.8	274	8.25, 7.50	12.2	311	522	6780	120	3075	830	6175	120	2800	830

Note: Wheel listed first is the measuring wheel.

(1) Exceeding the lawful speed limit is neither recommended nor endorsed.

(2) Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

(3) HS50 Wide Base Tread Design.

UNIROYAL® commercial truck tires and tubes are subject to a continuous development program. MNA, Inc. reserves the right to change product specifications at any time without notice or obligations.