

Application	LONG HAUL	REGIONAL AND URBAN/LAST MILE	ON/OFF ROAD
Position			
Steer/ All Position	<p>UNIROYAL® LS2 <i>Coming 2025</i></p>	<p>UNIROYAL® RS2 4 Year⁽²⁾ </p> <p>A Smartway® regional and last mile delivery steer tire offering from an affordable brand you know and trust, with a history of keeping America rolling for more than 125 years.</p> <p>Designed to:</p> <ul style="list-style-type: none"> Perform in high scrub environments with advanced compounds and deep tread Reduce irregular wear with the use of micro siping in the major grooves Reduce stone retention with a zig-zag channel groove and an angled groove wall Enhance wet traction with four large groove channels for water evacuation 	<p>UNIROYAL® HS2 4 Year⁽²⁾ </p> <p>A On/Off-Road, heavy-duty steer tire offering from an affordable brand you know and trust, with a history of keeping America rolling for more than 125 years.</p> <p>Designed to:</p> <ul style="list-style-type: none"> Perform in construction applications with advanced compounding that has chip and cut resistance Provide traction with deep tread and zig-zag groove design Reduce stone retention with a step-down groove wall design
Drive Axle	<p>UNIROYAL® LD2 4 Year⁽²⁾ </p> <p>A Smartway® line haul drive tire offering from an affordable brand you know and trust, with a history of keeping America rolling for more than 125 years.</p> <p>Designed to:</p> <ul style="list-style-type: none"> Provide fuel efficiency and mileage performance with the use of advanced compounding Provide long wear with 31/32" tread depth Grip the road with tread siping and zig-zag groove for traction Reduce stone drilling with the use of variable groove walls 	<p>UNIROYAL® RD2 4 Year⁽²⁾ </p> <p>A regional and last mile delivery drive tire offering from an affordable brand you know and trust, with a history of keeping America rolling for more than 125 years.</p> <p>Designed to:</p> <ul style="list-style-type: none"> Perform in regional scrub environments with advanced compounding and deep tread Provide enhanced traction with bridged open shoulder and siping Reduce irregular wear with block stabilizers, shoulder bridging, and a heel-toe inhibitor tread design Reduce stone retention with angled groove walls 	<p>UNIROYAL® HD2 4 Year⁽²⁾ </p> <p>A On/Off-Road, heavy-duty drive tire offering from an affordable brand you know and trust, with a history of keeping America rolling for more than 125 years.</p> <p>Designed to:</p> <ul style="list-style-type: none"> Perform in construction applications with advanced compounding that has chip and cut resistance Provide traction with an open shoulder, deep tread and zig zag groove design Reduce irregular wear with the use of supporting ridges and tie bar tread profile Reduce stone retention with a step-down groove wall design
Trailer Axle	<p>UNIROYAL® LT2 4 Year⁽²⁾ </p> <p>A Smartway® line haul and regional trailer tire offering from an affordable brand you know and trust, with a history of keeping America rolling for more than 125 years.</p> <p>Designed to:</p> <ul style="list-style-type: none"> Provide fuel efficiency and mileage performance in demanding trailer applications Reduce irregular wear with groove micro siping and supporting shoulder tread design Reduce stone retention with casing keepers in the major grooves Enhance water evacuation with the four groove design 		

(1) Based on internal tests against SmartWay® requirements. For more information on SmartWay® verified technologies, go to US: www.epa.gov/smartway or CA: <https://www.nrcan.gc.ca>.

(2) 4 Year / 2-Retreads Manufacturer's Limited Casing Guarantee. See limited warranty for details.

TECHNICAL DATA

Size	Tread	Load Range	Catalog Number	Tread Depth	Max. Speed (*)		Loaded Radius		Overall Diameter		Overall Width (#)		Approved Wheels (Measuring wheel listed first.)	Min. Dual Spacing (#)		Revs Per Mile	Max. Load and Pressure Single				Max. Load and Pressure Dual			
				32nds	mph	kph	in.	mm	in.	mm	in.	mm		in.	mm		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
215/75R17.5	RS2	H	54344	16	75	120	13.9	354	30.4	773	8.6	218	6.00, 6.75	9.3	237	685	4805	125	2180	850	4540	125	2060	850
225/70R19.5	RS2	G	07627	16	81	130	14.9	378	32.0	812	9.0	229	6.75, 6.00	10.0	254	649	3970	110	1800	760	3750	110	1700	760
	RD2	G	39486	19	81	130	15.0	382	32.2	818	9.0	228	6.75, 6.00	10.0	254	643	3970	110	1800	760	3750	110	1700	760
245/70R19.5	RS2	H	40450	17	81	130	15.3	389	33.0	839	9.8	248	7.50, 6.75	11.0	279	628	4940	120	2240	825	4675	120	2120	825
	RD2	H	36004	19	75	120	15.5	394	33.2	843	9.8	248	7.50, 6.75	11.0	279	624	4940	120	2240	825	4675	120	2120	825
11R22.5	LD2	H	33594	31	75	120	19.3	491	41.7	1060	10.5	267	8.25, 7.50	12.5	318	502	6610	120	3000	830	6005	120	2725	830
	LT2	H	30777	12	75	120	19.4	492	40.8	1037	10.4	265	8.25, 7.50	12.5	318	504	6610	120	3000	830	6005	120	2725	830
	RS2	H	11723	19	75	120	19.2	488	41.3	1048	10.7	273	8.25, 7.50	12.5	318	503	6610	120	3000	830	6005	120	2725	830
	RD2	H	70609	27	75	120	19.3	490	41.8	1061	10.7	273	8.25, 7.50	12.5	318	498	6610	120	3000	830	6005	120	2725	830
	HS2	H	16202	25	68	110	19.1	486	41.1	1043	10.7	273	8.25, 7.50	12.5	318	499	6610	120	3000	830	6005	120	2725	830
	HD2	H	29114	30	68	110	19.3	491	41.9	1064	10.7	273	8.25, 7.50	12.5	318	504	6610	120	3000	830	6005	120	2725	830
255/70R22.5	RS2	H	02838	18	81	130	17.0	431	36.5	927	10.4	264	7.50, 8.25	11.3	287	569	5510	120	2500	830	5070	120	2300	830
295/75R22.5	LD2	G	05234	31	75	120	19.5	495	40.8	1037	11.1	282	9.00, 8.25	13.2	335	503	6175	110	2800	760	5675	110	2575	760
	LT2	G	14609	12	75	120	18.7	476	39.4	1002	10.8	274	9.00, 8.25	13.2	335	521	6175	110	2800	760	5675	110	2575	760
	RS2	H	02291	19	75	120	18.6	473	39.9	1014	11.2	284	9.00, 8.25	13.2	335	519	6610	120	3000	830	6005	120	2725	830
	RD2	G	15050	27	75	120	19.1	485	40.6	1031	10.8	275	9.00, 8.25	13.2	335	509	6175	110	2800	760	5675	110	2575	760
315/80R22.5	HS2	L	88895	22	68	110	19.2	487	42.0	1068	12.4	316	9.00, 9.75	13.8	315	489	10200	130	4625	900	9090	130	4125	900
11R24.5	LT2	H	27443	12	75	120	20.1	511	42.5	1079	10.6	270	8.25, 7.50	12.5	318	485	7160	120	3250	830	6610	120	3000	830
	RS2	H	91876	19	75	120	20.4	519	43.2	1099	10.7	273	8.25, 7.50	12.5	318	477	7160	120	3250	830	6610	120	3000	830
	RD2	H	63317	27	75	120	20.7	526	43.7	1111	10.7	271	8.25, 7.50	12.5	318	471	7160	120	3250	830	6610	120	3000	830
	HS2	H	19800	25	68	110	20.1	511	43.1	1094	10.7	273	8.25, 7.50	12.5	318	479	7160	120	3250	830	6610	120	3000	830
	HD2	H	09361	29	68	110	20.3	516	43.8	1113	10.7	273	8.25, 7.50	12.5	318	481	7160	120	3250	830	6610	120	3000	830
285/75R24.5	LT2	G	30932	12	75	120	19.4	493	40.8	1037	10.9	276	8.25, 7.50	12.5	318	504	6175	110	2800	760	5675	110	2575	760
	RS2	H	09179	19	75	120	19.6	497	41.3	1048	10.8	274	8.25, 7.50	12.5	318	499	6780	120	3075	830	6175	120	2800	830
	RD2	G	11598	27	75	120	19.7	502	41.8	1061	10.8	275	8.25, 7.50	12.5	318	493	6175	110	2800	760	5675	110	2575	760

Note: Wheel listed first is the measuring wheel.

(1) Exceeding the lawful speed limit is neither recommended nor endorsed.

(2) Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

UNIROYAL® commercial truck tires and tubes are subject to a continuous development program. MNA, Inc. reserves the right to change product specifications at any time without notice or obligations. (06/23)